

## XXL-Rehab Shower commode

Strongly engineered and functionally designed exclusively for bariatric users!

We have aimed at designing the best shower commode on the market. It is designed for easy access, independence, safety and on the caregiver terms.

The inside width of the chair is 61 or 71 cm, but using a 5 cm high PU foam seat and 7 cm free space to the armrests allows the body mass to fall down, instead of fading out to the sides. The impossible "wide inside but small outside" is obtained. That makes the XXL-Rehab Shower commode passing nearly though all modern doorways.

The footrest is always the weak point when it comes to bariatric products. Normally the producer makes a short cut here, by using a standard solution. We did not only design the footrest to carry 100 kg each, we did more!

The footrest is also side/width adjustable, so access to intimate hygiene is possible and people with the fat-tissue placed on the inside of

their leg can sit with legs apart (up to 110 cm) and still have foot support. The brand new footrest is even nicely covered with PU foam.


One of the unique new features is a split toilet seat, a long open hole: 44 cm and 22 cm at the widest point. This to enable a correct use of the chair, it eases access for caregivers and avoids incidents where material ends up in places it wasn't meant to end up!

The ability for bariatric users to reach far back to reach the armrest is usually not present. Therefore we have made the armrests with a length of 64 cm and let it stick out 7 cm from the seat base, ready to welcome and support the hands of mobile users. It enables the user to get into the chair by him/herself. Another option is the butterfly armrests. Butterfly armrests add more than 10 cm to the seating width.

The space between backrest and seat has a clearance of 32 cm. This gives space for a possible bulbose gluteal region, but also enables the caregivers to reach for the sling and position the user better.



**Options:**  
Butterfly armrests,  
side/width adjustable  
footrest.



TURN PAGE →

SPECIFICATIONS	Model 1	Model 2
Maximum weight-bearing capacity is	325 kg	
Seat width	61 cm	71 cm
Seat depth	56 cm	
Seat height	55 cm	
Backrest	32-52 cm	
Total width	67 cm	77 cm
Seat to footrest	40-42-44-46-48 cm	
Width of footrest	58-110 cm	
Pushbar from floor	99 cm	
Width between armrests	54 cm	
Height of backrest	48 cm	
Height of footrests	40-48 cm	
Distance from floor to seat underside	44.5 cm	
Total length	112 cm	
Total weight	27 kg	
Wheels	125 mm (2 wheels with individual locks)	
Materials		
Seat	Pressure moulded PUR foam	
Frame	Powder-lacquered chromium molybdenum steel	
RAL Color Code	White RAL7035	
ISO classification	ISO 09 12 03	
Order No - standard	0150-061-000	0150-071-000
Order No - with butterfly armrests	0151-061-000	0151-071-000

*Powder coating and few tubings help protecting our environment and natural resources.*